



Easy on-site customization thanks to cuttable sections



Complete solution for indoor and outdoor applications



Quick and easy installation with self-adhesive backing

STRIP LED 24V

FEATURES

IP rating	IP20
IK rating	Other
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Self-Adhesive Backing	True
Strip type	Flexible tape

INSTALLATION INFORMATION

Input	24V DC
Maximum Ambient Temperature	-20 - 45 °C
Weight	0.07
Construction Material	Flexible Tape
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Maximum Running Length	5 m

PHOTOMETRICS @ 25°C

Product code	W	Colour	Beam	lm	lm/W	Energy
50041/2700K	10W/m	2700K	120	1260	126	A t G F
50041/C	10W/m	3000K	120	1390	139	A t G F
50041/F	10W/m	6000K	120	1674	167	A t G F
50041/N	10W/m	4000K	120	1520	152	A t G F
70002/2700K	4.8W/m	2700K	120	534	111	A t G F
70002/C	4.8W/m	3000K	120	562	117	A t G F
70002/F	4.8W/m	6000K	120	629	131	A t G F
70002/N	4.8W/m	4000K	120	629	131	A t G F
70042/2700K	7W/m	2700K	120	945	135	A t G F
70042/90/2700K	7W/m	2700K	120	837	120	A t G F

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

Suitable for residential, retail, hospitality and architectural projects

Uniform, dot-free illumination for premium visual comfort

High color accuracy ideal for retail displays and design-focused spaces

Flexible and adaptable to straight or curved surfaces

Cut 50mm



1.2mm

