



STRIP LED 48V

11W Ideal for atmospheric lighting with 11W/m

IP20 Ideal for living room and hallways with IP20 rating

110lm/W High efficacy up to 192lm/W

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

224 Led chips per metre

Available in 10m or 20m reels

FEATURES

| | |
|------------------------|------------------|
| IP rating | IP20 |
| IK rating | Other |
| CSP Switchable | Single CCT |
| Dimmable Option | Driver dependent |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Self-Adhesive Backing | True |
| Bespoke Lengths | Yes |
| Strip type | Flexible tape |

INSTALLATION INFORMATION

| | |
|-----------------------------|---------------|
| Input | 48V DC |
| Maximum Ambient Temperature | -20 - 45 °C |
| Weight | 0.192 |
| Construction Material | Flexible Tape |
| UK Bathroom Zone | N/A |
| Electric Class (1, 2, 3) | III |
| Maximum Running Length | 10 m |

PHOTOMETRICS @ 25°C

| Product code | W | Colour | Beam | lm | lm/W | Energy |
|----------------|-------|--------|------|------|------|---------|
| 48092/2700K/10 | 11W/m | 2700K | 120 | 1994 | 181 | A t G E |
| 48092/C/10 | 11W/m | 3000K | 120 | 1994 | 181 | A t G E |
| 48092/N/10 | 11W/m | 4000K | 120 | 2113 | 192 | A t G E |
| 48092/2700K/20 | 11W/m | 2700K | 120 | 1994 | 181 | A t G E |
| 48092/C/20 | 11W/m | 3000K | 120 | 1994 | 181 | A t G E |
| 48092/N/20 | 11W/m | 4000K | 120 | 2113 | 192 | A t G E |
| 48102/2700K/10 | 11W/m | 2700K | 120 | 1994 | 181 | A t G F |
| 48102/C/10 | 11W/m | 3000K | 120 | 1994 | 181 | A t G F |
| 48102/N/10 | 11W/m | 4000K | 120 | 2113 | 192 | A t G E |
| 48102/2700K/20 | 11W/m | 2700K | 120 | 1994 | 181 | A t G F |

WIRING INFORMATION

| | |
|-------------------------|----------|
| Cable / Flying Lead | N/A |
| Type of Wiring Required | Parallel |

Cut 62.5mm

1.2mm

