



STRIP LED FLEX 230V-48V-24V

FEATURES

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Self-Adhesive Backing	False
Bespoke Lengths	No
Strip type	Side bending

INSTALLATION INFORMATION

Input	24V DC
Maximum Ambient Temperature	-20 - 45 °C
Weight	0.85
Construction Material	Flexible Tape with Silicone Coating
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Maximum Running Length	5 m

PHOTOMETRICS @ 25°C

Product code	W	Colour	Beam	lm	lm/W
FL01/C	9.6W	3000K	110	276	29
FL01/F	9.6W	6000K	110	276	29
FL01/N	9.6W	4000K	110	276	29
FL02/C	11.5W	3000K	110	345	30
FL02/F	11.5W	6000K	110	345	30
FL02/N	11.5W	4000K	110	345	30
FL03/C	14.4W	3000K	150	996	69
FL03/F	14.4W	6000K	150	996	69
FL03/N	14.4W	4000K	150	996	69
FL04/C	11.5W	3000K	120	875	76

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

9.6W/m Ideal for atmospheric light with 9.6W/m

14.4W/m Ideal for primary light with 14.4W/m

IP67 Suitable for wet environments with IP67/IP65 rating

WARRANTY

Warranty 3 years

FEATURES & BENEFITS

High quality LED strip maintaining light quality and consistency

Available in 5m or 20m reels (depending on range)

CRI 80 providing true colour appearance

Cut 71.4mm



10mm



15mm