



## BORU 2

Linear LED Profile for 48V Track

### FEATURES

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

### INSTALLATION INFORMATION

Input	48V DC
Maximum Ambient Temperature	-20 - 40°C
Weight	0.179kg
Construction Material	Aluminium
Electric Class (1, 2, 3)	III
Mounting Options	On Track
Power Factor	0.95

### Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	Energy
TR44805	Matt black	40	21W	2700K	1360	65	
				3000K	1585	76	
				4000K	1505	72	

### WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

**21W** 21W

Colour switchable between 2700K, 3000K & 4000K

**IP20** IP20 perfect for interior applications

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

40° beam angle for precise illumination

SDCM3 ensuring uniform light appearance and consistency

CRI 90 providing true colour appearance

