



## TORO T

Decorative Opal Glass LED Globe for 48V Track

### FEATURES

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
Tiltable (°)	90
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation angle (°)	350

### INSTALLATION INFORMATION

Input	48V DC
Maximum Ambient Temperature	-20 - 40°C
Weight	0.249kg
Construction Material	Aluminium
Electric Class (1, 2, 3)	III
Mounting Options	On Track
Power Factor	0.95

### Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	Energy
TR46905	Matt black	230	5W	2700K	340	68	
				3000K	390	78	
				4000K	385	77	

### WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

**5W** 5W

Colour switchable between 2700K, 3000K & 4000K

Rotation angle of 350° to help suit any project

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

230° beam angle for wide illumination

IP20 perfect for interior applications

SDCM3 ensuring uniform light appearance and consistency

Adjustable with a 90° tilt

CRI 90 providing true colour appearance

