

 Colour temperature switchable, 3000K-4000K-6000K

 120lm/W Highly efficient up to 120 Llm/W ensures low running costs

 Quick and easy installation with plug & play connectors

## Thea Lite CSP 100mm

Colour Switchable IP54 Downlight

### Features

IP rating	IP54 (from below) IP20 (from above)
CSP Switchable	Switchable CCT
Sensor Option	On Request
Dimmable Option	Yes (DALI-2, 0-10V, PUSH-DIM)
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, using converter

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.361
Insulation Coverable	No
Inrush Current	4.2A 0.128ms
Cut Out Size	100
Construction Material	ADC12 Aluminium Housing, Polycarbonate+PET Diffuser, TP(a) Thermoplastic, Silicone Free
Electric Class (1, 2, 3)	2
Install Connector Type	Push-fit terminal, loop-in/loop-out
FR Building Regulations	Satisfait les essais au fil incandescent: 850°C
TP rating	TP(a)
Power Factor	0.5

### Guarantee


Warranty	5 years
Battery Warranty	3 years

### Features & benefits

- UGR27 compliant for comfortable lighting of washrooms, bathrooms, cloakrooms as well as general circulation and stairs
- IP54 protection against water splash from any direction
- Low 33mm product depth enables product to be used with small ceiling voids
- TP(a) Thermoplastic
- 850° Glow Wire Test

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
THL1X	White RAL9003	DALI-2 / 0-10V / Push-Dim	80°	10W	3000K	1100	110	See Accessories	
					4000K	1200	120	See Accessories	
					6000K	1200	120	See Accessories	
THL1T	White RAL9003	Mains dimmable	80°	10W	3000K	1100	110	See Accessories	
					4000K	1200	120	See Accessories	
					6000K	1200	120	See Accessories	
THLBIT	Matt Black RAL9005	Mains dimmable	80°	10W	3000K	1000	100	See Accessories	
					4000K	1100	110	See Accessories	
					6000K	1100	110	See Accessories	
THLBIX	Matt Black RAL9005	DALI-2 / 0-10V / Push-Dim	80°	10W	3000K	1000	100	See Accessories	
					4000K	1100	110	See Accessories	



					es
					See
		6000K	1100	110	Accessories
					es



## Wiring Information

Cable / Flying Lead	0.75-1.5mm <sup>2</sup>
Type of Wiring Required	Parallel

## Accessories

PS250600MA	Power supply, IP20, 13-29W, CC, 250-600mA, DALI-2, 1-10V, Push-Dim	Sold Separately
LEDEPI0	Emergency converter, Self-test, 220lm	Sold Separately
LEDEPI0DA	Emergency converter, DALI-2 Addressable	Sold Separately
EMRWMAN	Salvus Route White, Man-Test, 120lm(O) or 130lm(C)	Sold Separately
EMRWST	Salvus Route White, Self Test, 120lm(O) or 130lm(C)	Sold Separately

Our colour switchable commercial downlight is ideal for any commercial installation. In schools, gymnasiums, hotels, and offices. Also, with its IP54 rating, it is equipped to be installed externally and internally. Other benefits include a plug-and-play connector for quick and easy installation and 120 lm/W, which provides high efficiency and low running costs for an energy-saving light solution.