

142lm/W

Highly efficient 142 Lm/W ensures low running costs

IP65

IP65 protected as standard, suitable for bathroom zone 1

UGR19 or UGR22

UGR19 compliant low glare lighting when insert is used

WARRANTY

Warranty	5 years
Battery Warranty	3 years

FEATURES & BENEFITS

Circular economy design by Collingwood, enables the product to be disassembled quickly for easy upgrade of the LEDs and driver or recycling at end of life

TP(a) Thermoplastic

850° Glow Wire Test

2-part first/second fix connector available on request for easy maintenance

Thea Pro Suspension kit (THPSUSKITB or THPSUSKITW) is only suitable when used in conjunction with Thea Pro Surface kit (THPI2SURKITW, THP34SURKITW, THPI2SURKITB, THP34SURKITB)

THEA PRO 165-200MM

High Performance UGR19 (using insert accessory) Downlight

FEATURES

IP rating	IP65 (from below) IP20 (from above)
CSP Switchable	Single CCT
Tiltable (°)	Fixed
UGR	UGR<22
Sensor Option	On Request
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 80,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, using converter

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.55
Insulation Coverable	Luminaire: Rolled and blown insulation Driver: no
Inrush Current	6.9A 0.3ms
Cut Out Size	165-200
Construction Material	ADC12 Aluminium Housing, Polycarbonate+PET Diffuser, TP(a) Thermoplastic
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminal, loop-in/loop-out
FR Building Regulations	Satisfait les essais au fil incandescent: 850°C
TP rating	TP(a)
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
THP3N	White RAL9003	On-Off	80°	14W	4000K	2000	142	A t G B
THP4N		On-Off	80°	14W	4000K	2000	142	A t G B
				25W	4000K	3500	140	A t G B
THP3X	White RAL9003	Driverless	80°	14W	4000K	2000	142	A t G B
THP4X		Driverless	80°	14W	4000K	2000	142	A t G B
				25W	4000K	3500	140	A t G B

WIRING INFORMATION

Cable / Flying Lead	0.75-2.5mm ²
Type of Wiring Required	Parallel

ACCESSORIES

THP34UGR	Thea Pro, UGR19 Insert, THP3 + THP4	Sold Separately
THP23DD / THP4DD	Thea Pro, DALI-2 Driver, THP4 (THP4DD) THP3 (THP23DD)	Sold Separately
CASDRV25W	Casambi Wireless 25W Driver pre-wired with DC plug	Sold Separately
LEDEP10	Emergency converter, Self-test, 220lm	Sold Separately
LEDEP10DA	Emergency converter, DALI-2 Addressable	Sold Separately
DRV3001050	42W CC Driver, IP20, 300-1050mA	Sold Separately
THLDRVMDIM	TRIAC mains dimmable Driver for THP2 & THP3	Sold Separately
THP34SURKITW & THP34SURKITB	The Pro Surface Mount Kit for THP3 and THP4	Sold Separately

