

142lm/W

Highly efficient 142 Lm/W ensures low running costs

IP65

IP65 protected as standard, suitable for bathroom zone 1

UGR19 or UGR22

UGR19 compliant low glare lighting when insert is used

WARRANTY

Warranty	5 years
Battery Warranty	3 years

FEATURES & BENEFITS

Circular economy design by Collingwood, enables the product to be disassembled quickly for easy upgrade of the LEDs and driver or recycling at end of life

TP(a) Thermoplastic

850° Glow Wire Test

2-part first/second fix connector available on request for easy maintenance

THEA PRO 165-200MM

High Performance UGR19 (using insert accessory) Downlight

FEATURES

IP rating	IP65 (from below) IP20 (from above)
CSP Switchable	Single CCT
Tiltable (°)	Fixed
UGR	UGR<22
Sensor Option	On Request
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 80,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, using converter

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.55
Insulation Coverable	Luminaire: Rolled and blown insulation Driver: no
Inrush Current	6.9A 0.3ms
Cut Out Size	165-200
Construction Material	ADC12 Aluminium Housing, Polycarbonate+PET Diffuser, TP(a) Thermoplastic
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminal, loop-in/loop-out
FR Building Regulations	Satisfait les essais au fil incandescent: 850°C
TP rating	TP(a)
Power Factor	0.9

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
THP3N	White RAL9003	On-Off	14W	4000K	80°	2000	142	See Accessories	A B
THP4N		On-Off	25W	4000K	80°	3500	140	See Accessories	A B
THP3X	White RAL9003	Driverless	14W	4000K	80°	2000	142	See Accessories	A B
THP4X		Driverless	25W	4000K	80°	3500	140	See Accessories	A B

WIRING INFORMATION

Cable / Flying Lead	0.75-2.5mm ²
Type of Wiring Required	Parallel

ACCESSORIES

THP34UGR	Thea Pro, UGR19 Insert, THP3 + THP4	Sold Separately
THP23DD / THP4DD	Thea Pro, DALI-2 Driver, THP4 (THP4DD) THP3 (THP23DD)	Sold Separately
CASDRV25W	Casambi Wireless 25W Driver pre-wired with DC plug	Sold Separately
LEDEPI0	Emergency converter, Self-test, 220lm	Sold Separately
LEDEPI0DA	Emergency converter, DALI-2 Addressable	Sold Separately
DRV3001050	42W CC Driver, IP20, 300-1050mA	Sold Separately
THLDRVMDIM	TRIAC mains dimmable Driver for THP2 & THP3	Sold Separately

