



- IP67** IP67 for complete protection against ingress of dust & water
- IK10** IK08 (GLTM_11/14) IK10 (GLTM_16/19/22)
- Suitable for coastal applications

Tilt Adjustable Ground Light

Straight to Mains, DALI-2 dimmable

Features

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
Tiltable	25°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Weight	GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Inrush Current	GLTM_14: 0.55A 0.14ms, GLTM_16: 0.45A 0.5ms, GLTM_19: 0.025ms, GLTM_22: 0.5A 0.3ms
Cut Out Size	147
Construction Material	Anodised aluminium body, 316 SS bezel
UK Bathroom Zone	2
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 5 years

Features & benefits

- Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees
- Static loading capacity is 2000kg
- Pre-wired with 1 meter of cable to aid the installer
- TRIAC mains dimmable and RGBW options also available

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GLTMS147D30	Stainless steel 316	Ø147mm cut-out	10W	3000K	34°	1000	100	
GLTMS165D30	Stainless steel 316	Ø165mm cut-out	18W	3000K	34°	1600	89	
GLTMS193D30	Stainless steel 316	Ø193mm cut-out	23W	3000K	34°	2300	100	
GLTMS223D30	Stainless steel 316	Ø223mm cut-out	28W	3000K	34°	3300	100	

Wiring Information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 3x1.0mm ²
Type of Wiring Required	Parallel

Accessories

DM298FP	Faceplate rotary mains dimmer	Sold Separately
DM298GRID	Grid rotary mains dimmer	Sold Separately
JB5	Gel filled waterproof connector	Sold Separately

