




-  IP67 for complete protection against ingress of dust & water
-  IK08 (GLTM\_11/14) IK10 (GLTM\_16/19/22)
-  Suitable for coastal applications

## Tilt MGround TRIAC

Straight to Mains, TRIAC mains dimmable

### Features

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
Tilttable	25°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Inrush Current	GLTM_11: 0.5A 0.4ms, GLTM_14: 0.6A 0.4ms, GLTM_16: 0.45A 0.5ms, GLTM_19: 0.55A 0.5ms, GLTM_22: 0.55A 0.5ms
Cut Out Size	119
Construction Material	Anodised aluminium body, 316 SS bezel
UK Bathroom Zone	2
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### Guarantee

Warranty 5 years

### Features & benefits

- Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees
- Static loading capacity is 2000kg
- Pre-wired with 1 meter of cable to aid the installer
- DALI-2 dimmable and RGBW options also available

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GLTMS119T30	Stainless steel 316	Ø119mm cut-out	6W	3000K	34°	450	75	
GLTMS147T30	Stainless steel 316	Ø147mm cut-out	12W	3000K	34°	1200	100	
GLTMF147T30	Stainless steel 316	Ø147mm cut-out	12W	3000K	60°	1200	100	
GLTMS165T30	Stainless steel 316	Ø165mm cut-out	18W	3000K	34°	1600	89	
GLTMF165T30	Stainless steel 316	Ø165mm cut-out	18W	3000K	60°	1600	89	
GLTMS193T30	Stainless steel 316	Ø193mm cut-out	23W	3000K	34°	2300	100	
GLTMS223T30	Stainless steel 316	Ø223mm cut-out	30W	3000K	34°	3300	100	

### Wiring Information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 3x1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### Accessories

DM298FP	Faceplate rotary mains dimmer	Sold Separately
DM298GRID	Grid rotary mains dimmer	Sold Separately
JB5	Gel filled waterproof connector	Sold Separately

