



RGBW



IP67 for complete protection against ingress of dust & water



IK10 for protection against high impact

Tilt adjustable RGBW ground light

Driverless, RGBW Colour Change

Features

IP rating	IP67
IK rating	IK10
CSP Switchable	RGBW
Tilttable	25°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Cut Out Size	119
Construction Material	Anodised aluminium body, 316 SS bezel
UK Bathroom Zone	2
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Guarantee

Warranty 5 years

Features & benefits

- Suitable for coastal applications
- Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees
- Static loading capacity is 2000kg
- Pre-wired with 1 meter of cable to aid the installer
- TRIAC mains dimmable and DALI-2 dimmable options also available

RGBW Photometrics

Product Code	Type	Wattage	Colour	Beam Angle	lm	lm/W
GLTXS119RGBW	Ø119mm cut-out	2W	White (3000K)	40°	80	28
GLTXS119RGBW	Ø119mm cut-out	2W	Red	40°	60	26
GLTXS119RGBW	Ø119mm cut-out	2W	Green	40°	90	30
GLTXS119RGBW	Ø119mm cut-out	2W	Blue	40°	30	9
GLTXS147RGBW	Ø147mm cut-out	4W	White (3000K)	40°	160	28
GLTXS147RGBW	Ø147mm cut-out	3W	Red	40°	130	30
GLTXS147RGBW	Ø147mm cut-out	4W	Green	40°	190	37
GLTXS147RGBW	Ø147mm cut-out	4W	Blue	40°	60	11
GLTXS165RGBW	Ø165mm cut-out	5.5W	White (3000K)	40°	260	28
GLTXS165RGBW	Ø165mm cut-out	4.5W	Red	40°	190	30
GLTXS165RGBW	Ø165mm cut-out	5W	Green	40°	300	37
GLTXS165RGBW	Ø165mm cut-out	5W	Blue	40°	100	11
GLTXS193RGBW	Ø193mm cut-out	9W	White (3000K)	40°	360	28
GLTXS193RGBW	Ø193mm cut-out	7W	Red	40°	275	33
GLTXS193RGBW	Ø193mm cut-out	9W	Green	40°	400	37
GLTXS193RGBW	Ø193mm cut-out	9W	Blue	40°	150	12
GLTXS223RGBW	Ø223mm cut-out	11.5W	White (3000K)	40°	510	28
GLTXS223RGBW	Ø223mm cut-out	9W	Red	40°	380	39
GLTXS223RGBW	Ø223mm cut-out	11.5W	Green	40°	560	41
GLTXS223RGBW	Ø223mm cut-out	12W	Blue	40°	190	13

Wiring Information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 5x1.0mm2
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	4
CCDRV75DMX	220-240V	Yes	Yes	2	4
CCDRV75RF	220-240V	Yes	Yes	2	4

Accessories

JB5	Gel filled waterproof junction box	Sold Separately
-----	------------------------------------	-----------------

