



RGBW



IP67 for complete protection against ingress of dust & water



IK10 for protection against high impact

## WARRANTY

Warranty

5 years

## FEATURES & BENEFITS

Suitable for coastal applications

Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees

Static loading capacity is 2000kg

Pre-wired with 1 meter of cable to aid the installer

TRIAC mains dimmable and DALI-2 dimmable options also available

Supplied with installation tube



# TILT RGBW GROUND LIGHT

Driverless, RGBW Colour Change

## FEATURES


IP rating	IP67
IK rating	IK10
CSP Switchable	RGBW
Tiltable (°)	25
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)
Rotation angle (°)	Fixed

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Cut Out Size	119
Construction Material	Anodised aluminium body, 316 SS bezel
UK Bathroom Zone	2
SELV	N/A
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

## Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
GLTXS119RGBW	Stainless steel 316	Ø119mm cut-out	40°	2W	White (3000K)	80	28	
					Red	60	26	
					Green	90	30	
					Blue	30	9	
GLTXS147RGBW	Stainless steel 316	Ø147mm cut-out	40°	4W	White (3000K)	160	28	
					Red	130	30	
					Green	190	37	
					Blue	60	11	
GLTXS165RGBW	Stainless steel 316	Ø165mm cut-out	40°	5.5W	White (3000K)	260	28	
					Red	190	30	
					Green	300	37	
					Blue	100	11	
GLTXS193RGBW	Stainless steel 316	Ø193mm cut-out	40°	9W	White (3000K)	360	28	
					Red	275	33	
					Green	400	37	
					Blue	150	12	
GLTXS223RGBW	Stainless steel 316	Ø223mm cut-out	40°	11.5W	White (3000K)	510	28	
					Red	380	39	
					Green	560	41	
					Blue	190	13	



<b>Cable / Flying Lead</b>	Pre-wired 1.0M H05RN-F, 5x1.0mm2
<b>Type of Wiring Required</b>	Series

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	4
CCDRV75DMX	220-240V	Yes	Yes	2	4
CCDRV75RF	220-240V	Yes	Yes	2	4

## ACCESSORIES

<b>JB3 or JB7</b>	Junction box	Sold Separately
<b>CR575RGBW</b>	5-core PVC cable	Sold Separately



**COLLINGWOOD**  
LIGHTING

LIGHTING INNOVATION