Panels specification sheet



Trinity Versa 600x600

Direct/Indirect UGR19 Recessed Modular

Features	
IP rating	IP20
IK rating	IK03
CSP Switchable	Single CCT
UGR	19
Sensor Option	Plug-in PIR
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L70 50,000h
Colour Rendering Index	001.00
	CRI>80
Colour Consistency	SDCM6
Colour Consistency	
	SDCM6

Installation Information					
Input	220-240V AC				
Maximum Ambient Temperature	-20°C - 40°C				
Weight	3.8kg				
Insulation Coverable	No				
Inrush Current	28A <50ms				
Construction Material	Steel Housing, Prismatic				
	Diffuser, TP(a) Rated				
UK Bathroom Zone	N/A				
SELV	SELV				
Electric Class (1, 2, 3)	2				
Install Connector Type	Easy-fit connector				
TP rating	TP(a)				

Photometrics @ 25°C

Product Code	Туре	Beam	W	Colour	lm	lm/W	Energy
			13W	4000K	1900	146	A B
			16W	4000K	2500	156	
TRI66N40	On-Off	80°	18W	4000K	2800	156	
			20W	4000K	3100	155	
			25W	4000K	3700	148	
TRI66X40		80°	13W	4000K	1900	146	A B
			16W	4000K	2500	156	
	Driver excluded		18W	4000K	2700	150	
			20W	4000K	3100	155	
			25W	4000K	3900	156	

LED Driver

TRIDALIDRV

Accessories		
LEDEP10EM	Manual-test emergency converter	Sold Separately
LEDEP10	Self-test emergency converter	Sold Separately
LEDEP09DA	DALI (not DALI-2) emergency converter (DALI-2 coming in Jan 2025)	Sold Separately
TRIONOFFPIR	PIR on-off sensor including Easy-Fit Connector	Sold Separately
TRI010VPIR	Coming in Jan 2025	Sold Separately
TRIDALIPIR	DALI 2 PIR Sensor (exc connector, incoming cable needs to be split)	Sold Separately
TRIKITPULL	Bracket kit to allow modular to pull-up into ceiling	Sold Separately

Yes (Dali)





UGR19



Wattage switchable from 13W to




Ultra-efficient up to 156 Llm/W

Guarantee

Warranty 5 years **Battery Warranty** 5 years On-Site Warranty 2 years

Features & benefits

- Suitable for classroom, office and retail
- Direct/Indirect design provides a soft low glare lit effect
- TP(a) rated diffuser and 850-deg glow wire test approval, makes the product to be suitable for use in fire escape routes
- Plug-in PIR accessory to keep the light OFF when no-one is present
- Energy class B rating
- DALI-2 and PUSH-DIM driver options
- · Lay-in, pull-up into concealed ceilings, plasterboard recess
- Manual-test, self-test and DALI-2 test emergency options





220-240V