





TRINITY VERSA 600X600

Direct/Indirect UGR19 Recessed Modular

FEATURES

IP rating	IP20
IK rating	IK07
CSP Switchable	Single CCT
UGR	UGR<19
Sensor Option	Plug-in PIR
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Manual, Self and DALI-2
Emergency Option	Test

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	-20°C - 40°C		
Weight	3.36kg		
Insulation Coverable	No		
Inrush Current	13.8A 0.16ms		
Construction Material	Steel Housing, Prismatic		
Construction Material	Diffuser, TP(a) Rated		
UK Bathroom Zone	N/A		
SELV	Yes		
Electric Class (1, 2, 3)	II		
Install Connector Type	Easy-fit connector		
UK Building Regulations	Part P & L		
Mounting Options	Ceiling		
TP rating	TP(a)		
Power Factor	0.893		

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	Energy
TRI66N40 White On-Off	White	On-Off	80°	13W	4000K	1900	146	
				16W	4000K	2500	156	
				18W	4000K	2800	156	A B
			20W	4000K	3100	155		
		26W	4000K	3700	142			
TRI66X40	White	Driver excluded	80°	13W	4000K	1900	146	
				16W	4000K	2500	156	
				18W	4000K	2700	156	A B
				20W	4000K	3100	155	
				26W	4000K	3900	142	

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10EM	Manual-test emergency converter	Sold Separately
LEDEP10	Emergency converte, Self-test & Manual-test switchable	Sold Separately
LEDEP10DA	DALI-2 emergency converter (use with driver TRISDIMDRV)	Sold Separately
TRIONOFFPIR	PIR on-off sensor including Easy-Fit Connector	Sold Separately
TRISDIMPIR	Step-dim sensor (requires TRISDIMDRV)	Sold Separately
TRIDALIPIR	DALI 2 PIR Sensor (Requires TRIDALIDRV)	Sold Separately
TRIREMOTE	Remote controller for programming TRIONOFFPIR & TRISDIMPIR	Sold Separately
TRIKITPULL	Trinity Pull-up Mounting Kit	Sold Separately



LIGHTING INNOVATION



UGR19



Wattage switchable from 13W to 26W



Ultra-efficient up to 156 Llm/W

WARRANTY

Warranty 5 year
Battery Warranty 5 year
On-Site Warranty 2 year

FEATURES & BENEFITS

Suitable for classroom, office and retail applications

Direct/Indirect design provides a soft low glar lit effect

TP(a) rated diffuser and 850-deg glow wire test approval, makes the product to be suitable for use in fire escape routes

Plug-in PIR accessory to keep the light OFF when no-one is present

Energy class B rating

DALI-2 and PUSH-DIM driver options

Lay-in, pull-up into (up to 40mm) ceiling depths using TRIKITPULL $\,$

Manual-test, self-test and DALI-2 test emergency options



