



UGR19



Wattage switchable from
13W to 26W



Ultra-efficient up to 156
lm/W

TRINITY VERSA 600X600

Direct/Indirect UGR19 Recessed Modular

FEATURES

| | |
|------------------------|-----------------------------------|
| IP rating | IP20 |
| IK rating | IK07 |
| CSP Switchable | Single CCT |
| UGR | UGR<19 |
| Sensor Option | Plug-in PIR |
| Dimmable Option | Yes (DALI-2, PUSH-DIM) |
| LED Lifetime | L80 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM4 |
| Emergency Option | Yes, Manual, Self and DALI-2 Test |

INSTALLATION INFORMATION

| | |
|-----------------------------|--|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 40°C |
| Weight | 3.8kg |
| Insulation Coverable | No |
| Inrush Current | 13.8A 0.16ms |
| Construction Material | Steel Housing, Prismatic Diffuser, TP(a) Rated |
| UK Bathroom Zone | N/A |
| SELV | Yes |
| Electric Class (1, 2, 3) | 2 |
| Install Connector Type | Easy-fit connector |
| UK Building Regulations | Part P & L |
| Mounting Options | Ceiling |
| TP rating | TP(a) |
| Power Factor | 0.893 |

Photometrics @ 25°C

| Product Code | Finish | Type | Beam | W | Colour | lm | lm/W | Energy |
|--------------|--------|-----------------|------|-----|--------|------|------|------------------|
| TRI66N40 | White | On-Off | 80° | 13W | 4000K | 1900 | 146 | A t g B |
| | | | | 16W | 4000K | 2500 | 156 | |
| | | | | 18W | 4000K | 2800 | 156 | |
| | | | | 20W | 4000K | 3100 | 155 | |
| | | | | 26W | 4000K | 3700 | 142 | |
| TRI66X40 | White | Driver excluded | 80° | 13W | 4000K | 1900 | 146 | A t g B |
| | | | | 16W | 4000K | 2500 | 156 | |
| | | | | 18W | 4000K | 2700 | 156 | |
| | | | | 20W | 4000K | 3100 | 155 | |
| | | | | 26W | 4000K | 3900 | 142 | |

WIRING INFORMATION

| | |
|-------------------------|----------|
| Cable / Flying Lead | N/A |
| Type of Wiring Required | Parallel |

ACCESSORIES

| | | |
|-------------|--|-----------------|
| LEDEPI0EM | Manual-test emergency converter | Sold Separately |
| LEDEPI0 | Manual & Self-test switchable emergency converter | Sold Separately |
| LEDEPI0DA | DALI-2 emergency converter (use with driver TRISDIMDRV) | Sold Separately |
| TRIONOFFPIR | PIR on-off sensor including Easy-Fit Connector | Sold Separately |
| TRISDIMPIR | Step-dim sensor (requires TRISDIMDRV) | Sold Separately |
| TRIDALIPIR | DALI 2 PIR Sensor (Requires TRIDALIDRV) | Sold Separately |
| TRIREMOTE | Remote controller for programming TRIONOFFPIR & TRISDIMPIR | Sold Separately |
| TRIKITPULL | Trinity Pull-up Mounting Kit | Sold Separately |

WARRANTY

| | |
|------------------|---------|
| Warranty | 5 years |
| Battery Warranty | 5 years |
| On-Site Warranty | 2 years |

FEATURES & BENEFITS

Suitable for classroom, office and retail applications

Direct/Indirect design provides a soft low glare lit effect

TP(a) rated diffuser and 850-deg glow wire test approval, makes the product to be suitable for use in fire escape routes

Plug-in PIR accessory to keep the light OFF when no-one is present

Energy class B rating

DALI-2 and PUSH-DIM driver options

Lay-in, pull-up into (up to 40mm) ceiling depths using TRIKITPULL

Manual-test, self-test and DALI-2 test emergency options

BEAM ANGLE: 80°

