



## UL010

Universal LED light

### FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Tilttable (°)	360
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

### INSTALLATION INFORMATION

Input	150mA / 250mA / 350mA / 500mA / 700mA DC
Maximum Ambient Temperature	55°C
Weight	UL010A: 512g, UL010BK: 512g, UL010SS: 500g, UL010BZ: TBC
Inrush Current	N/A
Construction Material	Stainless Steel 316
UK Bathroom Zone	0
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
UL010SS22XF	Stainless steel	0.4W / 0.7W / 1W / 1.5W / 2.2W	2200K	40°	51 - 196	89 - 120	
UL010SS27XF	Stainless steel	0.4W / 0.7W / 1W / 1.5W / 2.2W	2700K	40°	51 - 196	89 - 120	
UL010SS30XF	Stainless steel	0.4W / 0.7W / 1W / 1.5W / 2.2W	3000K	40°	54 - 210	95 - 129	
UL010SS40XF	Stainless steel	0.4W / 0.7W / 1W / 1.5W / 2.2W	4000K	40°	60 - 234	106 - 143	
UL010AB22XF	Antique brass	0.4W / 0.7W / 1W / 1.5W / 2.2W	2200K	40°	51 - 196	89 - 120	
UL010AB27XF	Antique brass	0.4W / 0.7W / 1W / 1.5W / 2.2W	2700K	40°	51 - 196	89 - 120	
UL010AB30XF	Antique brass	0.4W / 0.7W / 1W / 1.5W / 2.2W	3000K	40°	54 - 210	95 - 129	
UL010AB40XF	Antique brass	0.4W / 0.7W / 1W / 1.5W / 2.2W	4000K	40°	60 - 234	106 - 143	

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A

## ACCESSORIES

<b>JB2 / JB4</b>	Waterproof junction box / Gel filled waterproof connector	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately



**COLLINGWOOD**  
LIGHTING

### LIGHTING INNOVATION

UL010 Modular is a versatile, swivel-mounted universal light that offers endless possibilities and ensures that any corner of a landscape can be lit, whether that's a pond, tree, or anything in-between. With a 360° stainless-steel bracket, 12° or 40° beam angle, IP68 water-resistance rating, and coastal protection, this feature light is a perfect addition. Available in new colours featuring stainless steel, bronze, black, and antique brass.