

3W at 700mA

Coastal protected

IP68 ideal for outdoor areas
and under water lighting

FEATURES & BENEFITS

Complete with wall fixings

Robust cable for use outdoors

Tilt & rotate for adjusting light

Long lifetime of 70,000hrs

UL010

Universal LED light

FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Tiltable (°)	360
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	700mA DC
Maximum Ambient Temperature	35°C
Weight	500g
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
UL010 NW	Stainless steel 316	Spot: 26°, Flood: 40°	3W	4000K	119	40	648	
UL010 A WW	Brass	26°	3W	3000K	95	32	411	
UL010 A 27	Brass	26°	3W	2700K	92	31	399	
UL010 B 27	Black anodised aluminium	26°	3W	2700K	92	31	399	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) rubberised cable (outside diameter: 6mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	3	9
PLD UNI-DRIVE 700mA		Yes	Yes (1-10V)	2	1	10
				2	1	10

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

26°