



3W at 700mA

Coastal protected

IP68 ideal for outdoor areas and under water lighting

UL010

Universal LED light

Features

IP rating	IP68
CSP Switchable	Single CCT
Tiltable	360°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	700mA
Maximum Ambient Temperature	35°C
Weight	500g
Construction Material	Stainless steel (316)
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Guarantee

Features & benefits

- Complete with wall fixings
- Robust cable for use outdoors
- Tilt & rotate for adjusting light
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
UL010 NW	Stainless steel 316	3W	4000K	26°	119	40	648	
UL010 WW	Stainless steel 316	3W	3000K	26°	95	32	411	
UL010 27	Stainless steel 316	3W	2700K	26°	92	31	399	
UL010 A WW	Brass	3W	3000K	26°	95	32	411	
UL010 A 27	Brass	3W	2700K	26°	92	31	399	
UL010 B 30	Black anodised aluminium	3W	3000K	26°	95	32	411	
UL010 B 27	Black anodised aluminium	3W	2700K	26°	92	31	399	

Wiring Information

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) rubberised cable (outside diameter: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	3	9
PLD UNI-DRIVE 700mA		Yes	Yes (1-10V)	2	1	10
				2	1	10

Accessories

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

