

3W

3W at 700mA



Coastal protected

IP68

IP68 ideal for outdoor areas
and under water lighting

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Complete with wall fixings

Robust cable for use outdoors

Tilt & rotate for adjusting light

Long lifetime of 70,000hrs

UL010

Universal LED light

FEATURES

| | |
|------------------------|------------------|
| IP rating | IP68 |
| CSP Switchable | Single CCT |
| Tilttable (°) | 360 |
| Dimmable Option | Driver dependent |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation angle (°) | 360 |

INSTALLATION INFORMATION

| | |
|-----------------------------|-----------------------------------------------------|
| Input | 700mA DC |
| Maximum Ambient Temperature | 35°C |
| Weight | 500g |
| Inrush Current | N/A |
| Construction Material | Stainless steel (316), brass, anodised aluminium |
| UK Bathroom Zone | 0 |
| SELV | N/A |
| Electric Class (1, 2, 3) | III |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Photometrics @ 25°C

| Product Code | Finish | Beam | W | Colour | lm | lm/W | lx@1m | Energy |
|--------------|-----------------------------|--------------------------|----|--------|-----|------|-------|--------|
| UL010 NW | Stainless steel 316 | Spot: 26°, Flood: 40° | 3W | 4000K | 119 | 40 | 648 | |
| UL010 A WW | Brass | 26° | 3W | 3000K | 95 | 32 | 411 | |
| UL010 A 27 | Brass | 26° | 3W | 2700K | 92 | 31 | 399 | |
| UL010 B 27 | Black anodised aluminium | 26° | 3W | 2700K | 92 | 31 | 399 | |

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| | |
|-------------------------|-------------------------------------------------------|
| Cable / Flying Lead | 3m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | (H05RN-F) rubberised cable (outside diameter: 6mm) |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|------------|----------|------|-------------|---------------|-----|-----|
| PSIP70018W | 220-240V | Yes | No | 0 | 1 | 8 |
| PSDIM700 | 220-240V | | Yes (1-10V) | 0 | 1 | 18 |

ACCESSORIES

| | | |
|-----------------|-----------------------------------------------------------|-----------------|
| JB2 / JB4 | Waterproof junction box / Gel filled waterproof connector | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |
| WCR 275 BLACK | 2-core rubber cable | Sold Separately |

