



# UL010RGBW COLOUR CHANGE

Colour change LED light (5W max.)

## FEATURES

IP rating	IP67
CSP Switchable	RGBW
Tilttable (°)	360
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Rotation angle (°)	360

## INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	700g
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

## RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL010RGBW	1.1W	White (4000K)	40°	50	45	101
UL010RGBW	1W	Red	40°	38	38	75
UL010RGBW	1.1W	Green	40°	63	57	124
UL010RGBW	1.1W	Blue	40°	11	8	17

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 5 CORE, 8MM OD

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

## ACCESSORIES

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately



RGBW



Coastal protected



IP67 ideal for outdoor areas  
and under water lighting

## WARRANTY

Warranty 5 years

## FEATURES & BENEFITS

- Complete with wall fixings for easy installation
- Can rotate and be angled to direct light
- Separate white LED for permanent use
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments

BEAM ANGLE: 40°

