



4.6W at 700mA



Coastal protected



IP68 ideal for outdoor areas and under water lighting

UL030

High output universal LED light

Features

| | |
|------------------------|------------------|
| IP rating | IP68 |
| CSP Switchable | Single CCT |
| Tiltable | 360° |
| Dimmable Option | Driver dependent |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation Angle | 360° |

Installation Information

| | |
|-----------------------------|--|
| Input | 700mA |
| Maximum Ambient Temperature | 50°C |
| Weight | 645g |
| Inrush Current | N/A |
| Construction Material | Stainless steel (316), brass, anodised aluminium |
| UK Bathroom Zone | 0 |
| Electric Class (1, 2, 3) | 3 |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Complete with wall fixings
- Tilt & rotate for adjusting light
- Antique brass finish, Marine grade stainless steel 316 & Black anodised aluminium
- Long lifetime of 70,000hrs

Photometrics @ 25°C

| Product Code | Finish | Beam | W | Colour | lm | lm/W | lx@1m | Energy |
|--------------|--------------------------|------|------|--------|-----|------|-------|--------|
| UL030DNBX40 | Stainless steel | 12° | 4.6W | 4000K | 490 | 70 | 7975 | AIG E |
| UL030DNBX30 | Stainless steel | 12° | 4.6W | 3000K | 480 | 69 | 7812 | AIG E |
| UL030DNBX27 | Stainless steel | 12° | 4.6W | 2700K | 470 | 67 | 7649 | AIG E |
| UL030DWBX27 | Stainless steel | 40° | 4.6W | 2700K | 470 | 67 | 1007 | AIG E |
| UL030DWBX30 | Stainless steel | 40° | 4.6W | 3000K | 480 | 69 | 1029 | AIG E |
| UL030DWBX40 | Stainless steel | 40° | 4.6W | 4000K | 490 | 70 | 1050 | AIG E |
| UL030ANAX30 | Brass | 12° | 4.6W | 3000K | 480 | 69 | 7812 | AIG E |
| UL030ANAX27 | Brass | 12° | 4.6W | 2700K | 470 | 67 | 7649 | AIG E |
| UL030AWAX30 | Brass | 40° | 4.6W | 3000K | 480 | 69 | 1029 | AIG E |
| UL030AWAX27 | Brass | 40° | 4.6W | 2700K | 470 | 67 | 1007 | AIG E |
| UL030BWBX30 | Black anodised aluminium | 40° | 4.6W | 3000K | 480 | 69 | 1029 | AIG E |
| UL030BWBX27 | Black anodised aluminium | 40° | 4.6W | 2700K | 470 | 67 | 1007 | AIG E |

Wiring Information


| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-------------|----------|------|-------------|---------------|-----|-----|
| PLU/700 3-9 | 220-240V | Yes | No | 0 | 1 | 4 |
| PSIP70018W | 220-240V | Yes | No | 0 | 1 | 3 |
| PSDIM700 | 220-240V | | Yes (1-10V) | 0 | 1 | 11 |

Accessories

| | | |
|-----------------|---|-----------------|
| JB2 / JB4 | Waterproof junction box / Gel filled waterproof connector | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |



Feature lights specification sheet

| | | |
|---------------------|----------------------------|-----------------|
| WCR 275 BLACK | 2-core rubber cable | Sold Separately |
| PLD UNI-DRIVE 700MA | 700mA Driver | Sold Separately |
| PLD UNI-DRIVE 700MA | IP65 700mA 2W - 18W Driver | Sold Separately |



collingwood

This versatile, swivel-mounted universal light offers endless possibilities and ensures that any corner of a landscape can be lit, whether that's a pond, tree or anything in-between. With a 360° stainless-steel bracket, 12° beam angle, IP68 water-resistance rating and bright 4.6W LED light output equivalent to a 35W halogen, it throws light into even the darkest and wettest environments.