



4.6W at 700mA



Coastal protected



IP68 ideal for outdoor areas and under water lighting

UL030

High output universal LED light

Features

IP rating	IP68
CSP Switchable	Single CCT
Tiltable	360°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	700mA
Maximum Ambient Temperature	50°C
Weight	645g
Inrush Current	N/A
Construction Material	Stainless steel (316), brass, anodised aluminium
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Complete with wall fixings
- Tilt & rotate for adjusting light
- Antique brass finish, Marine grade stainless steel 316 & Black anodised aluminium
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
UL030DNBX40	Stainless steel	4.6W	4000K	12°	490	70	7975	
UL030DNBX30	Stainless steel	4.6W	3000K	12°	480	69	7812	
UL030DNBX27	Stainless steel	4.6W	2700K	12°	470	67	7649	
UL030DWBX27	Stainless steel	4.6W	2700K	40°	470	67	1007	
UL030DWBX30	Stainless steel	4.6W	3000K	40°	480	69	1029	
UL030DWBX40	Stainless steel	4.6W	4000K	40°	490	70	1050	
UL030ANAX30	Brass	4.6W	3000K	12°	480	69	7812	
UL030ANAX27	Brass	4.6W	2700K	12°	470	67	7649	
UL030AWAX30	Brass	4.6W	3000K	40°	480	69	1029	
UL030AWAX27	Brass	4.6W	2700K	40°	470	67	1007	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	0	1	4
PSIP70018W	220-240V	Yes	No	0	1	3
PSDIM700	220-240V		Yes (1-10V)	0	1	11

Accessories

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PLD UNI-DRIVE 700MA	700mA Driver	Sold Separately
PLD UNI-DRIVE 700MA	IP65 700mA 2W - 18W Driver	Sold Separately

