



4.6W 4.6W at 700mA

Coastal protected

IP68 IP68 ideal for outdoor areas and under water lighting

UL030

High output universal LED light

FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Tilttable (°)	360
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	700mA DC
Maximum Ambient Temperature	50°C
Weight	645g
Inrush Current	N/A
Construction Material	Stainless steel (316), brass, anodised aluminium
UK Bathroom Zone	0
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Complete with wall fixings

Tilt & rotate for adjusting light

Antique brass finish, Marine grade stainless steel 316 & Black anodised aluminium

Long lifetime of 70,000hrs

PATENT: **GB2544975 EP3176502**

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
UL030DNBX40	Stainless steel	12°	4.6W	4000K	490	70	7975	
UL030DNBX27	Stainless steel	12°	4.6W	2700K	470	67	7649	
UL030DWBX30	Stainless steel	40°	4.6W	3000K	480	69	1029	
UL030DWBX40	Stainless steel	40°	4.6W	4000K	490	70	1050	
UL030ANAX30	Brass	12°	4.6W	3000K	480	69	7812	
UL030ANAX27	Brass	12°	4.6W	2700K	470	67	7649	
UL030AWAX30	Brass	40°	4.6W	3000K	480	69	1029	
UL030AWAX27	Brass	40°	4.6W	2700K	470	67	1007	
UL030BWBX30	Black anodised aluminium	40°	4.6W	3000K	480	69	1029	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION



Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	3
PSDIM700	220-240V		Yes (1-10V)	0	1	11

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



PLD UNI-DRIVE 700MA	700mA Driver	Sold Separately
PLD UNI-DRIVE 700MA	IP65 700mA 2W - 18W Driver	Sold Separately



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

This versatile, swivel-mounted universal light offers endless possibilities and ensures that any corner of a landscape can be lit, whether that's a pond, tree or anything in-between. With a 360° stainless-steel bracket, 12° beam angle, IP68 water-resistance rating and bright 4.6W LED light output equivalent to a 35W halogen, it throws light into even the darkest and wettest environments.