



collingwood



4.6W at 700mA



Coastal protected



IP68 ideal for outdoor areas and under water lighting

UL030

Features

IP rating	IP68
CSP Switchable	Single CCT
Tiltable	360°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	700mA
Maximum Ambient Temperature	50°C
Weight	645g
Inrush Current	N/A
Construction Material	Stainless steel (316), brass, anodised aluminium
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Complete with wall fixings
- Tilt & rotate for adjusting light
- Antique brass finish, Marine grade stainless steel 316 & Black anodised aluminium
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
UL030DNBX40	Stainless steel	12°	4.6W	4000K	490	70	7975	AIG E
UL030DNBX30	Stainless steel	12°	4.6W	3000K	480	69	7812	AIG E
UL030DNBX27	Stainless steel	12°	4.6W	2700K	470	67	7649	AIG E
UL030DWBX27	Stainless steel	40°	4.6W	2700K	470	67	1007	AIG E
UL030DWBX30	Stainless steel	40°	4.6W	3000K	480	69	1029	AIG E
UL030DWBX40	Stainless steel	40°	4.6W	4000K	490	70	1050	AIG E
UL030ANAX30	Brass	12°	4.6W	3000K	480	69	7812	AIG E
UL030ANAX27	Brass	12°	4.6W	2700K	470	67	7649	AIG E
UL030AWAX30	Brass	40°	4.6W	3000K	480	69	1029	AIG E
UL030AWAX27	Brass	40°	4.6W	2700K	470	67	1007	AIG E
UL030BWBX30	Black anodised aluminium	40°	4.6W	3000K	480	69	1029	AIG E
UL030BWBX27	Black anodised aluminium	40°	4.6W	2700K	470	67	1007	AIG E

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver


Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	0	1	4
PSIP70018W	220-240V	Yes	No	0	1	3
PSDIM700	220-240V		Yes (1-10V)	0	1	11

Accessories

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

Patent Information

GB25444975 EP3176502



PLD UNI-DRIVE 700MA

700mA Driver

Sold Separately

PLD UNI-DRIVE 700MA

IP65 700mA 2W - 18W Driver

Sold Separately



collingwood

This versatile, swivel-mounted universal light offers endless possibilities and ensures that any corner of a landscape can be lit, whether that's a pond, tree or anything in-between. With a 360° stainless-steel bracket, 12° beam angle, IP68 water-resistance rating and bright 4.6W LED light output equivalent to a 35W halogen, it throws light into even the darkest and wettest environments.