



UL030RGBW

Colour change LED light (12W max.)

Features

IP rating	IP67
CSP Switchable	RGBW
Tiltable	360°
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Rotation Angle	360°

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	900g
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL030RGBW	3W	White (4000K)	45°	177	59	154
UL030RGBW	2W	Red	45°	106	53	60
UL030RGBW	3W	Green	45°	185	62	168
UL030RGBW	3W	Blue	45°	43	14	1

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 5 CORE, 8MM OD

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	4
CCDRV75DMX	220-240V	Yes	Yes	2	4
CCDRV75RF	220-240V	Yes	Yes	2	4

Accessories

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately



collingwood



RGBW



Coastal protected



IP67 ideal for outdoor areas and under water lighting

Guarantee

Warranty 5 years

Features & benefits

- Complete with wall fixings for easy installation
- Can rotate and be angled to direct light
- Separate white LED for permanent use
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments

Patent Information

GB2487912 GB2512715

Beam angle: 45°

