



## UL345CARGB

110° colour change wall washing light bar (12W max.)

### Features

IP rating	IP65
IK rating	IK02
CSP Switchable	RGB
Tilttable	180°
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h

### Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	0.7kg
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

### RGB Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL345CARGB	4W	Red	110°	96	24	32
UL345CARGB	4.1W	Green	110°	161	39	57
UL345CARGB	4.3W	Blue	110°	51	12	19

### Wiring Information

Cable / Flying Lead	1x 3m LED RGB 0.75mm <sup>2</sup> cable (outside diameter: 6mm)
Input Cable Type	H05RN-F 4 CORE, 6MM OD

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

### Accessories

JB3	Waterproof junction box	Sold Separately
CCRFCONWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately
ULBRACKET	2 piece black anodised aluminium bracket	Sold Separately



collingwood



RGB



Coastal protected



IP65 ideal for outdoor environments

### Guarantee

Warranty 5 years

### Features & benefits

- Surface mount in multiple applications
- Compatible with a large range of controllers
- Anodised aluminium for use in outdoor and indoor environments
- Removable feet can be used anywhere along the base or sides. Allen key included

