



collingwood



RGB



Coastal protected



IP65 ideal for outdoor environments

UL347CARGB

Features		Installation Information	
IP rating	IP65	Input	350mA
IK rating	IK02	Maximum Ambient Temperature	35°C
CSP Switchable	RGB	Weight	0.7kg
Tilttable	180°	Construction Material	Anodised aluminium
Dimmable Option	Driver dependent	UK Bathroom Zone	1
LED Lifetime	L50 50,000h	Electric Class (1, 2, 3)	3
Rotation Angle	No	Suitable for coastal areas	Yes

Guarantee

Warranty 5 years

Features & benefits

- Surface mount in multiple applications
- Compatible with a large range of controllers
- Anodised aluminium for use in outdoor and indoor environments
- Removable feet can be used anywhere along the base or sides. Allen key included

RGB Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL347CARGB	4W	Red	45°	77	19	175
UL347CARGB	4.1W	Green	45°	285	70	535
UL347CARGB	4.3W	Blue	45°	51	12	90

Wiring Information

Cable / Flying Lead	1x 3m LED RGB 0.75mm ² cable (outside diameter: 6mm)
Input Cable Type	H05RN-F 4 CORE, 6MM OD

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

Accessories

JB3	Waterproof junction box	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately
ULBRACKET	2 piece black anodised aluminium bracket	Sold Separately

