



RGB



Coastal protected



IP65 ideal for outdoor environments

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Surface mount in multiple applications

Compatible with a large range of controllers

Anodised aluminium for use in outdoor and indoor environments

Removable feet can be used anywhere along the base or sides. Allen key included



UL347CARGB

45° colour change wall washing light bar (12W max.)

FEATURES

IP rating	IP65
IK rating	IK02
CSP Switchable	RGB
Tiltable	180°
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h
Rotation Angle	No

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	0.7kg
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

RGB Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL347CARGB	4W	Red	45°	77	19	175
UL347CARGB	4.1W	Green	45°	285	70	535
UL347CARGB	4.3W	Blue	45°	51	12	90

WIRING INFORMATION

Cable / Flying Lead	1x 3m LED RGB 0.75mm ² cable (outside diameter: 6mm)
Input Cable Type	H05RN-F 4 CORE, 6MM OD

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

ACCESSORIES

JB3	Waterproof junction box	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately
ULBRACKET	2 piece black anodised aluminium bracket	Sold Separately

