



RGB



Coastal protected



IP65 ideal for outdoor environments

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Surface mount in multiple applications

Compatible with a large range of controllers

Anodised aluminium for use in outdoor and indoor environments

Removable feet can be used anywhere along the base or sides. Allen key included



UL347CARGB

45° colour change wall washing light bar (12W max.)

FEATURES

| | |
|--------------------|------------------|
| IP rating | IP65 |
| IK rating | IK02 |
| CSP Switchable | RGB |
| Tiltable (°) | 180 |
| Dimmable Option | Driver dependent |
| LED Lifetime | L50 50,000h |
| Rotation angle (°) | Fixed |

INSTALLATION INFORMATION

| | |
|-----------------------------|--------------------|
| Input | 350mA DC |
| Maximum Ambient Temperature | 35°C |
| Weight | 0.7kg |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | 1 |
| Electric Class (1, 2, 3) | III |
| Suitable for coastal areas | Yes |

RGB Photometrics

| Product Code | Wattage | Colour | Beam Angle | lm | lm/W | lx @ 1m |
|--------------|---------|--------|------------|-----|------|---------|
| UL347CARGB | 4W | Red | 45° | 77 | 19 | 175 |
| UL347CARGB | 4.1W | Green | 45° | 285 | 70 | 535 |
| UL347CARGB | 4.3W | Blue | 45° | 51 | 12 | 90 |

WIRING INFORMATION

| | |
|---------------------|---|
| Cable / Flying Lead | 1x 3m LED RGB 0.75mm ² cable (outside diameter: 6mm) |
| Input Cable Type | H05RN-F 4 CORE, 6MM OD |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Max |
|-------------|----------|------|------------|---------------|-----|
| CCDRV75DALI | 220-240V | Yes | Yes (Dali) | 2 | 1 |
| CCDRV75DMX | 220-240V | Yes | Yes | 2 | 1 |
| CCDRV75RF | 220-240V | Yes | Yes | 2 | 1 |

ACCESSORIES

| | | |
|--|---|-----------------|
| JB3 | Waterproof junction box | Sold Separately |
| CR575RGBW | 5-core PVC cable | Sold Separately |
| CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W) | 4/8 zone RF control for RGB & RGBW system | Sold Separately |

