



## Uniform 4ft

1200mm Surface Linear

### Features

IP rating	IP44 (ceiling surface mount) IP40 (suspended or wall mounted)
IK rating	IK08
CSP Switchable	Single CCT
UGR	22
Sensor Option	Bolt-On PIR
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 70,000h
Colour Rendering Index	CRI>80
Emergency Option	Yes, Self-Test

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	3.2kg
Inrush Current	15.4A 0.48ms
Construction Material	Carbon Sheet Steel Housing, Polycarbonate Diffuser
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Surface
Power Factor	0.9

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
UNL4SN	White RAL9016	Standard	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	-	A B
UNL4SNE	White RAL9016	Emergency	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	325	A B
UNL4SD	White RAL9016	DALI-2 dimmable	30W	4000K	120°	4500	150	-	A B
UNL4SDE	White RAL9016	Emergency DALI-2 dimmable	30W	4000K	120°	4500	150	325	A B

### Wiring Information

Cable Required for Connector	Mains Cable
Type of Wiring Required	Parallel

### Accessories

PIRBOLT	On-off PIR sensor with daylight switch	Sold Separately
EMBOLTMOPEN	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTMCOR	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTSOPEN	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately
EMBOLTSCOR	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately



collingwood



Wattage switchable between 20W, 23W, 26W & 30W



Ultra-efficient up to 150 Llm/W



Quick and easy installation with Push-fit terminal

### Guarantee

Warranty	5 years
Battery Warranty	3 years

### Features & benefits

- Outstanding uniform lit effect
- 70,000 hours L80 lifetime
- IP44 rated allows the product to be used in a wide range of applications
- Bolt-on range of lighting controls and emergency conversion packs to aid fast availability
- RG0 (Risk Exempt) Photo-biological Risk
- Suspension kit available (UNLSUS2M)

