



Uniform 6ft

1800mm Surface Linear

Features

IP rating	IP44 (ceiling surface mount)
	IP40 (suspended or wall mounted)
IK rating	IK08
CSP Switchable	Single CCT
UGR	22
Sensor Option	Bolt-On PIR
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Self-Test

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	4.6kg
Inrush Current	15.4A 0.48ms
Construction Material	Carbon Sheet Steel
	Housing, Polycarbonate Diffuser
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Surface
Power Factor	0.90

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
UNL6SN	White RAL9016	Standard	20W -	4000K	120°	2822	150 - 150	-	A B
			23W -			3383			
			26W -			3984			
			30W			4500			
UNL6SNE	White RAL9016	Emergency	20W -	4000K	120°	2822	150 - 150	325	A B
			23W -			3383			
			26W -			3984			
			30W			4500			
UNL6SD	White RAL9016	DALI-2 dimmable	30W	4000K	120°	4500	150	-	A B
UNL6SDE	White RAL9016	Emergency DALI-2 dimmable	30W	4000K	120°	4500	150	325	A B

Wiring Information

Cable Required for Connector	Mains Cable
Type of Wiring Required	Parallel

Accessories

PIRBOLT	On-off PIR sensor with daylight switch	Sold Separately
EMBOLTMOPEN	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTMCOR	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTSOPEN	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately
EMBOLTSOR	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately



collingwood



Wattage switchable between 20W, 23W, 26W & 30W



Ultra-efficient up to 150 Llm/W



Quick and easy installation with Push-fit terminal

Guarantee

Warranty	5 years
Battery Warranty	3 years

Features & benefits

- Outstanding uniform lit effect
- 70,000 hours L80 lifetime
- IP44 rated allows the product to be used in a wide range of applications
- Bolt-on range of lighting controls and emergency conversion packs to aid fast availability
- RGO (Risk Exempt) Photo-biological Risk
- Suspension kit available (UNLSUS2M)

