



collingwood



Wattage switchable 30W, 35W, 40W & 45W, 4500lm to 6750lm



Ultra-efficient up to 150 Llm/W



UGR19 compliant low glare lighting

Features

IP rating	IP44
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR<19, UGR<22
Sensor Option	Versabox, see accessories
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Manual, Self and DALI-2 Test

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	4.2kg
Inrush Current	24A 354us
Construction Material	White RAL9003, Carbon Sheet Steel Housing, PMMA Diffuser (650°C)
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part P & L
Mounting Options	Surface
Power Factor	0.90

Guarantee

Warranty	7 years
Battery Warranty	5 years
On-Site Warranty	2 years

Features & benefits

- Outstanding uniform lit effect
- 70,000 hours L80 lifetime
- RG0 (Risk Exempt) Photo-biological Risk
- Versabox plug and play kit range to accommodate project requirements
- Suspension kit available (UNLSUS2M)

Photometrics @ 25°C


Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
UNV5N40	White RAL9003	Standard non-dimmable	80°	30W	4000K	4500	150	-	A B
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5NE40	White RAL9003	Emergency Non-dimmable	80°	30W	4000K	4500	150	230	A B
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	
UNV5NM40	White RAL9003	Microwave sensor non-dimmable	80°	30W	4000K	4500	150	-	A B
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5NME40	White RAL9003	Emergency microwave sensor non-dimmable	80°	30W	4000K	4500	150	230	A B
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	
UNV5D40	White RAL9003	DALI-2 dimmable	80°	30W	4000K	4500	150	-	A B
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5DE40	White RAL9003	Emergency DALI-2 dimmable	80°	30W	4000K	4500	150	230	A B
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	

Wiring Information

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

Accessories

UNVKITMANEM	Manual Test Emergency plug-in Versabox	Sold Separately
-------------	--	-----------------



UNVKITSELFEM	Self Test Emergency plug-in Versabox	Sold Separately
UNVKITDALIEM	DALI-2 Emergency plug-in Versabox	Sold Separately
UNVKITMWS	Microwave Sensor on/off plug-in Versabox	Sold Separately
UNREMOEMWS	Remote for Microwave Sensor	Sold Separately
PIRBOLT	On-off PIR sensor with daylight switch	Sold Separately
PIRBOLTDIM	PIR Bolt-on Sensor Step-Dim (requires 0-10V driver)	Sold Separately



Our surface linear light uniform is adaptable and highly efficient, producing up to 150 lm/W. It is the perfect product for any commercial setting, such as a hotel, office, or school. With its ability to be surface-mounted or suspended/wall-mounted, this energy-efficient light may be used in a variety of settings. Plus, with the use of a wattage switch, you can select your power at the time of installation, allowing you to make all of those critical decisions on-site.