



UNIFORM VERSA 5FT

Wattage Switchable UGR19 Linear with plug-in Versabox accessories

FEATURES

IP rating	IP44
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR19
Sensor Option	Versabox, see accessories
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Manual, Self and DALI-2 Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	4.2kg
Inrush Current	24A 354us
Construction Material	White RAL9003, Carbon Sheet Steel Housing, PMMA Diffuser (650°C)
SELV	No
Electric Class (1, 2, 3)	I
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part P & L
Mounting Options	Surface
Power Factor	0.90



Wattage switchable 30W, 35W, 40W & 45W, 4500lm to 6750lm



Ultra-efficient up to 150 lm/W



UGR19 compliant low glare lighting

WARRANTY

Warranty	7 years
Battery Warranty	5 years
On-Site Warranty	2 years

FEATURES & BENEFITS

Outstanding uniform lit effect

70,000 hours L80 lifetime

RG0 (Risk Exempt) Photo-biological Risk


Versabox plug and play kit range to accommodate project requirements

Suspension kit available (UNLSUS2M)

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
UNV5N40	White RAL9003	Standard non-dimmable	80°	30W	4000K	4500	150	-	
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5NE40	White RAL9003	Emergency Non-dimmable	80°	30W	4000K	4500	150	230	
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	
UNV5NM40	White RAL9003	Microwave sensor non-dimmable	80°	30W	4000K	4500	150	-	
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5NME40	White RAL9003	Emergency microwave sensor non-dimmable	80°	30W	4000K	4500	150	230	
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	
UNV5D40	White RAL9003	DALI-2 dimmable	80°	30W	4000K	4500	150	-	
				35W	4000K	5250	150	-	
				40W	4000K	6000	150	-	
				45W	4000K	6750	150	-	
UNV5DE40	White RAL9003	Emergency DALI-2 dimmable	80°	30W	4000K	4500	150	230	
				35W	4000K	5250	150	230	
				40W	4000K	6000	150	230	
				45W	4000K	6750	150	230	

80°



WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

ACCESSORIES

UNVKITMANEM	Manual Test Emergency plug-in Versabox	Sold Separately
UNVKITSELFEM	Self Test Emergency plug-in Versabox	Sold Separately
UNVKITDALIEM	DALI-2 Emergency plug-in Versabox	Sold Separately
UNVKITMWS	Microwave Sensor on/off plug-in Versabox	Sold Separately
UNREMOTEMWS	Remote for Microwave Sensor	Sold Separately
PIR Bolt-on Sensor Step-Dim (requires 0-10V driver)	PIR Bolt-on Sensor Step-Dim (requires 0-10V driver)	Sold Separately
CASBOLT7W	Casambi Wireless M20 Conduit Entry PIR+DL White 7m (requires 0-10V driver)	Sold Separately



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

Our surface linear light uniform is adaptable and highly efficient, producing up to 150 lm/W. It is the perfect product for any commercial setting, such as a hotel, office, or school. With its ability to be surface-mounted or suspended/wall-mounted, this energy-efficient light may be used in a variety of settings. Plus, with the use of a wattage switch, you can select your power at the time of installation, allowing you to make all of those critical decisions on-site.