


40W 40W

IP65 IP65 ideal for outdoor environments

 Suitable for use in coastal applications

WARRANTY

Warranty 7 years

FEATURES & BENEFITS


Plug and play through-wire install method

Supplied with waterproof connectors for fast install

3000K and 2700K range with choice of 2000 or 4200 lumen output

Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°

Also available in 500mm



VOLTA 1000MM

Wall washing light bar







FEATURES

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Tiltable (°)	180
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	2.5kg
Inrush Current	15A @10ms
Construction Material	Anodised aluminium
UK Bathroom Zone	1
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes
Mounting Options	Ceiling & wall

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LL1000MT30	Silver	40W	3000K	30°	4200	105	10745	
LL1000WT30	Silver	40W	3000K	60°	4200	105	4251	
LL1000AT30	Silver	40W	3000K	20x35°	4200	105	10860	
LL1000MT27	Silver	40W	2700K	30°	4200	105	10745	
LL1000WT27	Silver	40W	2700K	60°	4200	105	4251	
LL1000AT27	Silver	40W	2700K	20x35°	4200	105	10860	

WIRING INFORMATION

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

ACCESSORIES

N/A (No Accessories required)

