



collingwood



40W



IP65 ideal for outdoor environments



Suitable for use in coastal applications

## Volta 1000mm

Wall washing light bar

### Features

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	2.5kg
Inrush Current	15A @10ms
Construction Material	Anodised aluminium
UK Bathroom Zone	1
SELV	SELV
Electric Class (1, 2, 3)	2
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### Guarantee

Warranty 7 years

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LL1000MT30	Silver	40W	3000K	30°	4200	105	10745	
LL1000WT30	Silver	40W	3000K	60°	4200	105	4251	
LL1000AT30	Silver	40W	3000K	20x35°	4200	105	10860	
LL1000MT27	Silver	40W	2700K	30°	4200	105	10745	
LL1000WT27	Silver	40W	2700K	60°	4200	105	4251	
LL1000AT27	Silver	40W	2700K	20x35°	4200	105	10860	

### Wiring Information

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

### Accessories

N/A	No accessories required
-----	-------------------------

### Features & benefits

- Plug and play through-wire install method
- Supplied with waterproof connectors for fast install
- 3000K and 2700K range with choice of 2000 or 4200 lumen output
- Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°
- Also available in 500mm

