



collingwood



40W



IP65 ideal for outdoor environments



Suitable for use in coastal applications

Volta 1000mm

Wall washing light bar

Features

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Tiltable	180°
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	2.5kg
Inrush Current	15A @10ms
Construction Material	Anodised aluminium
UK Bathroom Zone	1
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Plug and play through-wire install method
- Supplied with waterproof connectors for fast install
- 3000K and 2700K range with choice of 2000 or 4200 lumen output
- Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°
- Also available in 500mm

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LL1000MT30	Silver	40W	3000K	30°	4200	105	10745	
LL1000WT30	Silver	40W	3000K	60°	4200	105	4251	
LL1000AT30	Silver	40W	3000K	20x35°	4200	105	10860	
LL1000MT27	Silver	40W	2700K	30°	4200	105	10745	
LL1000WT27	Silver	40W	2700K	60°	4200	105	4251	
LL1000AT27	Silver	40W	2700K	20x35°	4200	105	10860	

Wiring Information

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

Accessories

N/A (No Accessories required)

