



C
collingwood

21W

21W

IP65

IP65 ideal for outdoor environments



Suitable for use in coastal applications

Volta 500mm

Wall washing light bar

Features

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Tilttable	180°
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	1.4kg
Inrush Current	0.56A 18.8ms
Construction Material	Anodised aluminium
UK Bathroom Zone	1
SELV	SELV
Electric Class (1, 2, 3)	2
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Plug and play through-wire install method
- Supplied with waterproof connectors for fast install
- 3000K and 2700K range with choice of 2000 or 4200 lumen output
- Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°
- Also available in 1000mm

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LL500MT30	Silver	21W	3000K	30°	2000	95	5249	
LL500MT27	Silver	21W	2700K	30°	2000	95	5249	
LL500WT30	Silver	21W	3000K	60°	2000	95	1877	
LL500WT27	Silver	21W	2700K	60°	2000	95	1877	
LL500AT30	Silver	21W	3000K	20x35°	2000	95	5122	
LL500AT27	Silver	21W	2700K	20x35°	2000	95	5122	

Wiring Information

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------

