




**21W** 21W

**IP65** IP65 ideal for outdoor environments

 Suitable for use in coastal applications

## VOLTA 500MM

Wall washing light bar

### FEATURES

<b>IP rating</b>	IP65
<b>IK rating</b>	IK04
<b>CSP Switchable</b>	Single CCT
<b>Tiltable (°)</b>	180
<b>Dimmable Option</b>	Yes (Mains)
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	50°C
<b>Weight</b>	1.4kg
<b>Inrush Current</b>	0.56A 18.8ms
<b>Construction Material</b>	Anodised aluminium
<b>UK Bathroom Zone</b>	1
<b>SELV</b>	Yes
<b>Electric Class (1, 2, 3)</b>	I
<b>Earth Leakage</b>	0.1
<b>Suitable for coastal areas</b>	Yes
<b>Mounting Options</b>	Ceiling & wall

### WARRANTY

Warranty 7 years

### FEATURES & BENEFITS

Plug and play through-wire install method







Supplied with waterproof connectors for fast install

3000K and 2700K range with choice of 2000 or 4200 lumen output

Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°

Also available in 1000mm

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LL500MT30	Silver	21W	3000K	30°	2000	95	5249	
LL500MT27	Silver	21W	2700K	30°	2000	95	5249	
LL500WT30	Silver	21W	3000K	60°	2000	95	1877	
LL500WT27	Silver	21W	2700K	60°	2000	95	1877	
LL500AT30	Silver	21W	3000K	20x35°	2000	95	5122	
LL500AT27	Silver	21W	2700K	20x35°	2000	95	5122	

30°

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
<b>Type of Wiring Required</b>	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

### ACCESSORIES

N/A (No Accessories required)

