



Versa Tile Black 1500mm

UGR19 architectural linear

Features

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
UGR	19
Sensor Option	PIR & Daylight with accessories
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Self-Test

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 40°C
Weight	4.25kg
Inrush Current	Standard: 16A 672ms, DALI: 30A 45ms
Construction Material	Aluminium Housing, Polystyrene Diffuser
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall & suspended
Power Factor	0.95

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
VTBIN	Black RAL9005	Standard	45W	4000K	80	4500	100	-	A+ B D
VTBINEM	Black RAL9005	Emergency	45W	4000K	80	4500	100	215	A+ B D
VTBINP	Black RAL9005	PIR sensor	45W	4000K	80	4500	100	-	A+ B D
VTBID	Black RAL9005	DALI-2 dimmable	45W	4000K	80	4500	100	-	A+ B D
VTBIDP	Black RAL9005	DALI-2 Dimmable PIR Sensor	45W	4000K	80	4500	100	-	A+ B D
VTBIDEM	Black RAL9005	Emergency DALI-2 dimmable	45W	4000K	80	4500	100	215	A+ B D
VTBIDPEM	Black RAL9005	Emergency DALI-2 Dimmable PIR Sensor	45W	4000K	80	4500	100	215	A+ B D
VTBINPEM	Black RAL9005	Emergency	45W	4000K	80	4500	100	215	A+ B D

Wiring Information

Cable / Flying Lead	0.75-2.5mm ²
Type of Wiring Required	Parallel

Accessories

VTBWALL	Black Wall Mount Kit	Sold Separately
VTBCON	Black Connect Joint Kit	Sold Separately



collingwood



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

Guarantee

Warranty	7 years
Battery Warranty	5 years

Features & benefits

- Energy efficient up to 100lm/W
- Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)
- Suspend as an individual luminaire or (by custom request) connect together to make a continuous run
- >10% upright when surface mounted
- Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options
- DALI-2 driver is switchable to enable lower lumen outputs

