



Versa Tile Silver 1500mm

UGR19 architectural linear

Features

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
UGR	19
Sensor Option	PIR & Daylight with accessories
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Self-Test

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 40°C
Weight	4.25kg
Inrush Current	Standard: 16A 672ms, DALI: 30A 45ms
Construction Material	Aluminium Housing, Polystyrene Diffuser
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall & suspended
Power Factor	0.95

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
VTSIN	Silver	Standard	45W	4000K	80	5000	110	-	A A G D
VTSINEM	Silver	Emergency	45W	4000K	80	5000	110	240	A A G D
VTSIDEM	Silver	Emergency DALI-2 dimmable	45W	4000K	80	5000	110	240	A A G D
VTSIDP	Silver	DALI-2 Dimmable PIR Sensor	45W	4000K	80	5000	110	-	A A G D
VTSIDPEM	Silver	Emergency DALI-2 Dimmable PIR Sensor	45W	4000K	80	5000	110	240	A A G D
VTSID	Silver	DALI-2 dimmable	45W	4000K	80	5000	110	-	A A G D
VTSINP	Silver	PIR sensor	45W	4000K	80	5000	110	-	A A G D
VTSINPEM	Silver	Emergency	45W	4000K	80	5000	110	240	A A G D

Wiring Information

Cable / Flying Lead	0.75-2.5mm ²
Type of Wiring Required	Parallel

Accessories

VTSWALL	Silver Wall Mount Kit	Sold Separately
VTSCON	Silver Connect Joint Kit	Sold Separately



collingwood



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

Guarantee

Warranty	7 years
Battery Warranty	5 years

Features & benefits

- Energy efficient up to 110lm/W
- Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)
- Suspend as an individual luminaire or (by custom request) connect together to make a continuous run
- >10% upright when surface mounted
- Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options
- DALI-2 driver is switchable to enable lower lumen outputs

