



## Versa Tile White 1500mm

UGR19 architectural linear

### Features

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
UGR	UGR<19, UGR<22
Sensor Option	PIR & Daylight with accessories
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L80 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Self-Test

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 40°C
Weight	4.25kg
Inrush Current	Standard: 16A 672ms, DALI: 30A 45ms
Construction Material	Aluminium Housing, Polystyrene Diffuser
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall & suspended
Power Factor	0.95

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
VTWIN	Matt white RAL9003	Standard	45W	4000K	80	5500	120	-	
VTWINEM	Matt white RAL9003	Emergency	45W	4000K	80	5500	120	260	
VTWIDEM	Matt white RAL9003	Emergency DALI-2 dimmable	45W	4000K	80	5500	120	260	
VTWIDP	Matt white RAL9003	DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5500	120	-	
VTWIDPEM	Matt white RAL9003	Emergency DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5500	120	260	
VTWID	Matt white RAL9003	DALI-2 dimmable	45W	4000K	80	5500	120	-	
VTWINP	Matt white RAL9003	PIR sensor	45W	4000K	80	5500	120	-	
VTWINPEM	Matt white RAL9003	Emergency	45W	4000K	80	5500	120	260	

### Wiring Information

Cable / Flying Lead	0.75-2.5mm <sup>2</sup>
Type of Wiring Required	Parallel

### Accessories

VTWWALL	White Wall Mount Kit	Sold Separately
VTWCON	White Connect Joint Kit	Sold Separately



collingwood



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

### Guarantee

Warranty	7 years
Battery Warranty	5 years

### Features & benefits

- Energy efficient up to 120lm/W
- Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)
- Suspend as an individual luminaire or (by custom request) connect together to make a continuous run
- >10% uplight when surface mounted
- Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options
- DALI-2 driver is switchable to enable lower lumen outputs
- Supplied with suspension kit
- DALI Dimmable Fitting with on-off PIR Sense

