



11W

11W



Integral bracket for easy installation

IP54

IP54 ideal for framing doorways and entrances

WL012

IP54, 610lm straight to mains wall light

Features

| | |
|------------------------|-------------|
| IP rating | IP54 |
| IK rating | IK04 |
| CSP Switchable | Single CCT |
| Dimmable Option | No |
| LED Lifetime | L70 30,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM5 |

Installation Information

| | |
|-----------------------------|-------------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 1kg |
| Inrush Current | 20A 0.5ms |
| Construction Material | Powder coated aluminium |
| UK Bathroom Zone | N/A |
| SELV | SELV |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | No |

Guarantee

Warranty 5 years

Photometrics @ 25°C

| Product Code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------|-------|--------|------|-----|------|---------|--------|
| WL012X30 | Black RAL9011 | 11.0W | 3000K | 338° | 610 | 55 | 72 | |
| WL012G30 | Grey RAL7022 | 11.0W | 3000K | 338° | 610 | 55 | 72 | |

Wiring Information

| | |
|-------------------------|----------|
| Cable / Flying Lead | N/A |
| Type of Wiring Required | Parallel |

LED Driver

| Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-------|------|---------|---------------|-----|-----|
| - | Yes | No | - | - | - |

Accessories

| | |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|

Features & benefits

- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Provides a good light level for safe navigation at night
- Wide light distribution with 360° beam angle

