




**11W** 11W

 Integral bracket for easy installation

**IP54** IP54 ideal for framing doorways and entrances

## WL012

IP54, 610lm straight to mains wall light

### FEATURES

IP rating	IP54
IK rating	IK04
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1kg
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	No
Mounting Options	Wall

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS



Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Provides a good light level for safe navigation at night

Wide light distribution with 360° beam angle

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL012X30	Black RAL9011	11W	3000K	338°	610	55	72	
WL012G30	Grey RAL7022	11W	3000K	338°	610	55	72	

### WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

### LED DRIVER

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

### ACCESSORIES

N/A (No Accessories required)

