



11W

11W



Integral bracket for easy installation

IP54

IP54 ideal for framing doorways and entrances

WL012

IP54, 610lm straight to mains wall light

Features

IP rating	IP54
IK rating	IK04
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1kg
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

Guarantee

Warranty 5 years

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL012X30	Black RAL9011	11.0W	3000K	338°	610	55	72	
WL012G30	Grey RAL7022	11.0W	3000K	338°	610	55	72	

Wiring Information

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

LED Driver

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

Accessories

N/A	No accessories required
-----	-------------------------

Features & benefits

- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Provides a good light level for safe navigation at night
- Wide light distribution with 360° beam angle

