



# WL013

IP65, 390lm up-down wall light

#### **FEATURES**

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	467g
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	
Earth Leakage	0.1
Suitable for coastal areas	No
Mounting Options	Wall

#### PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL013X30	Black RAL9011	6.5W	3000K	107°/91°	390	60	99	A G
WL013G30	Grey RAL7022	6.5W	3000K	107°/91°	390	60	99	A G

#### WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

## LED DRIVER

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

#### **ACCESSORIES**

N/A	No accessories required	



LIGHTING INNOVATION



6.5W



Integral bracket for easy installation



IP65 ideal for outdoor environments

### WARRANTY

Warrant

5 years

## FEATURES & BENEFITS

Ideal for framina doorways and entrances

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Up & down light for creating a feature or perimeters and entrances

Sleek curved design

