



Black
WL014X

Grey
WL014G

WL014

IP54, 350lm cone up-down wall light

FEATURES

IP rating	IP54
IK rating	IK04
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	750g
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	No

PHOTOMETRICS @ 25°C

Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
Black RAL9011	5.7W	3000K	22°/26°	350	61	1061	

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

LED DRIVER

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

ACCESSORIES

N/A	No accessories required
-----	-------------------------

5.7W

5.7W



Integral bracket for easy installation

IP54

IP54 ideal for framing doorways and entrances

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Narrow upper beam and wide lower beam provides both decorative and functional light

Provides a good amount of light for safe navigation at night

Integral bracket for easy installation

