

13W

13W



Integral bracket for easy installation

IP65

IP65 ideal for outdoor environments

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Ideal for columns and entrances

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Up & down light for creating a feature of perimeters and entrances

Up to 1000lm, makes this an ideal choice for columns and tall surfaces



WL015

IP65, 1,000lm up-down wall light

FEATURES

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	800g
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL015X30	Black RAL9011	13W	3000K	88°	1000	77	362	
WL015G30	Grey RAL7022	13W	3000K	88°	1000	77	362	

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

LED DRIVER

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

ACCESSORIES

N/A	No accessories required
-----	-------------------------

