



## WL015

IP65, 1,000lm up-down wall light

### FEATURES

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	800g
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	No
Mounting Options	Wall

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL015X30	Black RAL9011	13W	3000K	88°	1000	77	362	

### WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

### LED DRIVER

Input	SELV	Dimming	Bathroom Zone	Min	Max
-	Yes	No	-	-	-

### ACCESSORIES

N/A	No accessories required
-----	-------------------------

- 13W** 13W
- Integral bracket for easy installation
- IP65** IP65 ideal for outdoor environments

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

- Ideal for columns and entrances
- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Up & down light for creating a feature of perimeters and entrances
- Up to 1000lm, makes this an ideal choice for columns and tall surfaces

