

# **WL041IP**

### **Features** IP rating IP65 **CSP** Switchable Single CCT Tiltable No Dimmable Option No L70 70,000h **LED Lifetime** Colour Rendering Index CRI>80 Colour Consistency SDCM3 **Rotation Angle**

Installation Information				
Input	220-240V AC			
Maximum Ambient Temperature	35°C			
Weight	0.3kg			
Inrush Current	9A 0.8ms			
Cut Out Size	N/A			
Construction Material	Anodised aluminium			
UK Bathroom Zone	2			
Electric Class (1, 2, 3)	1			
Suitable for coastal areas	Vas			

### Photometrics @ 25°C

Product Code	Finish	W	Colour	lm	lm/W	Lx @ 1m	Energy
WL041 IP NW	Silver	1.6W	4000K	37	23	8	A F
WL041 IP WW	Silver	1.6W	3000K	33	21	6	A F

## **Wiring Information**

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

### **LED Driver**

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

### **Accessories**

N/A (No Accessories required)

# collingwood



1.6W



Coastal protected




IP65 ideal for outdoor environments

### Guarantee

Warranty 7 years

### Features & benefits

- Unique radial appearance creates a decorative lit effect on surrounding surfaces
- Straight to mains for easy installation
- Complete with bracket and waterproof crimp



ongwoodlighting