

WL041IP

Straight to mains, fan effect LED wall light

FEATURES

| IP rating | IP65 | |
|------------------------|-------------|--|
| CSP Switchable | Single CCT | |
| Dimmable Option | No | |
| LED Lifetime | L70 70,000h | |
| Colour Rendering Index | CRI>80 | |
| Colour Consistency | SDCM3 | |
| | | |

INSTALLATION INFORMATION

| Input | 220-240V AC |
|-----------------------------|--------------------|
| Maximum Ambient Temperature | 35°C |
| Weight | 0.3kg |
| Inrush Current | 9A 0.8ms |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | 2 |
| Electric Class (1, 2, 3) | 1 |
| Suitable for coastal areas | Yes |

PHOTOMETRICS @ 25°C

| Product code | Finish | w | Colour | lm | lm/W | Lx @ 1m | Energy |
|--------------|--------|------|--------|----|------|---------|-------------|
| WL041 IP NW | Silver | 1.6W | 4000K | 37 | 23 | 8 | A f G |
| WL041 IP WW | Silver | 1.6W | 3000K | 33 | 21 | 6 | A F |

WIRING INFORMATION

| Cable / Flying Lead | 0.3m |
|-------------------------|----------|
| Type of Wiring Required | Parallel |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|------------------------------|----------|------|---------|---------------|-----|-----|
| N/A (integrated SELV driver) | 220-240V | Yes | No | N/A | N/A | N/A |

ACCESSORIES

No accessories required



LIGHTING INNOVATION

1.60

Coastal protected

IP65 ideal for outdoor environments

FEATURES & BENEFITS

Unique radial appearance creates a decorative lit effect on surrounding surfaces

Straight to mains for easy installation

Complete with bracket and waterproof crimp connectors